## OFFICE OF THE PRINCIPAL, B.B.COLLEGE, BAIGANBADIA, MAYURBHANJ

No. BBC-321/25

Dt.26.03.2025

## **QUOTATION CALL NOTICE**

Sealed quotations are invited within **17** days from the authorized dealer of having valid GST No, PAN, TIN, ID with Xerox copies of Authorization letter for supply of the following items.

## **SPECIFICATION**

SI.No	Item	Qty
1	1.13 and above Desktop	12 Nos
2	UPS	12 Nos
3	MFM Printer	2 Nos
4	Wireless Mice and Camera for virtual meeting	1 No

The above mentioned items must contain as per the specification attached herewith.

Principal

B.B.College, Baiganbadia

Mayurbhanj

PRINCIPAL

B.B. College, Baiganbadia Mayurbhanj

Memo No. BBC-322/25, Dt.26.03.2025.

Copy to General Notice Board/ Bursar Accounts/ Head Clerk for information and necessary action.

Principal

B.B.College, Baiganbadia

Mayurbhanj

PRINCIPAL B.B. College, Baiganbadia Mayurbhanj

Desktop :	Specification
Items	Specification
Cabinet Form Factor	Tower/Micro Tower (15.1 to 26 Litres)
Chipset Number	Intel H670/Intel® H770 or higher Chipset
Processor Make	Intel
Processor	x86 64-bit architecture
Processor Generation	15 Or higher
Processor Description	Intel Core i5 or higher
Processor Number	Intel Core i5 13100 or higher
Number of Cores and Threads per Processor	Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8 Threads or higher
Operating System	Windows 11 Home Factory Preloaded
RAM Size (GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)
RAM Expandability up to (using spare DIMM Slots in GB)	128 GB or higher
Integrated Graphics	Intel UHD Graphics 770 or higher
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Yes
Type of Drives used to populate the Internal Bays	NVMe SSD
Total HDD Capacity (GB)	NA
Total SSD Capacity (GB)	512GB NVMe SSD
Optical Drive	Optional
Orive Bays	Two 3.5" (2.5") HDD
Slots for Upgradation	1 PCI Express 4.0 x16, 1 PCI Express 3.0 x1, 1 PCI (Full Height), 2 M.2 slots for WLAN & SSD
LAN	LAN: Integrated 10/100/1000M
Ports and Connectors	Front: 1 headphone/microphone combo; 3 Super Speed USB 5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0
Firmware Trusted Platform Module	TPM 2.0
Hardware Security lock slot	Security lock slot
Power Supply	180-260Watt Internal power supply with minimum 90% efficiency
	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM i required.
	OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate
Certification	Microsoft Windows, Energy star 8.0 certified
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate of products at the time of participation of the Bid.
Keyboard Mouse	USB Keyboard; USB Optical Mouse
Monitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM
Years of Warranty	3 Year Onsite Warranty

	V-14-40-40-40-40-40-40-40-40-40-40-40-40-40	eractive UPS Specifications General Specifications	
SI. No.	Feature	General Specifications	
1	UPS Capacity (total)	600VA/360W	
2	Input Voltage	230 VAC nominal	
3	Input Frequency	45 - 65 Hz	
4	Brownout Transfer	145 VAC typical	
5	Over-voltage Transfer	290 VAC typical	
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)	
7	Frequency – On Battery	50Hz typical	
8	Transfer Time	@50 Hz 6 ms typical, 10 ms max	
9	Air Ventilation	Should have Side and Back Honey bee Perforation for heat dispersion	
10	Protection from Humidity & Dust	UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity	
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years	
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
13	AC Surge Protection	Full time, 160 joules	
14	Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference.	
15	Type (maintenance-free)	12V, 7.2 Ah	
16	Typical recharge time	4- 6 hours	
17	Operating Temperature	0°C to 40°C	
18	Storage Temperature	-15°C to 45°C	
19	3 power outlets	With battery backup and surge protection	
20	Power Cord	1.2 meters	
21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)	
22	Runtime for Workstation PC (100W ±15W)	13 min (normal mode)	
23	Battery Saver (to save on battery life)	Thru toggle button on front panel	
24	Certification	BIS	
25	Designed and Manufactured in India	Yes	
26	Warranty	2yeasrs	

×

	Generic	
Description of Stores	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter	
Core Function	Print, Scan and Copy	
Print Technology	Laser	
Cartridge Technology	Composite Cartridge	
Type of Printing	Monochrome (Black)	
RAM Size (MB)	256	
Storage Capacity (in GB)	0	
Features	Fax	
Operating System Compatibility	Windows 10 and Above,Linux,Mac OS,Windows Server	
	Printing	
Print Paper Size	A4 and Legal	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	26 to 30	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	Not Applicable	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Mono (in PPM)	Not Applicable	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Color (in PPM)	Not Applicable	
Auto Duplexing Printing/Coping (2-sided Feature)	Yes	
	Scanning	
Maximum Scan Area	A4 and Legal	
(Platen/Flatbed Size)	on anti-company contrant and the second and the sec	
A4 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpi	11 to 20	
Scan To Functions	Email	
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 20	
	COPYING	
Reduction and Enlargement	Yes	

	PAPER HANDLING
Original Document Feeder Type (For Scanning and Copying)	Automatic Document Feeders (ADF)
Feeder Capacity (Number of Sheets) (For Scanning and Copying)	31 to 40
Number of Main Paper Tray	1
Total Paper Tray Combined Capacity (Number) at 75 GSM	101 to 200
Bypass Tray Facility	No
If Yes, Bypass Tray Capacity	0
Connectivity	
Connectivity	USB Port,Ethernet Port,Wi-Fi
Accessories Provided	USB Cable
	Performance
Cartridge/Ink/Toner supplied with Machine as per IS/ISO/IEC: 19752/2017 for Black (Number of Prints)	
Minimum Yield of the Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	0
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000
	POWER
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz
Maximum Power Consumption (in Watt)	1300
Environmental	
Minimum Operating Temperature (Degree C)	10
Maximum Operating Temperature (Degree C)	30

Minimum Operating Humidity (%RH)	20	
Maximum Operating Humidity (%RH)	80	
	Dimension	
Standard Machine Weight with Single Tray (in Kg)	11	
	Certification	
BIS CRS Compliance	Yes as per IS 13252 (Part 1)	
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000	
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes	
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes	

		ELECTRIC TO ANNUAL PROPERTY AND
	Screen Size	65
	Brightness (cd/m²)	350Nits or better
	Contrast Ratio	1200:1
	Dynamic Contrast Ratio	400,000:1
General Features	Response Time (ms)	8.0
	Display resolution (H x V, pixels)	3840 x 2160
	HDR (High Dynamic Range) compatibility	Yes (HDR10, HLG)
	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
	Backlight type	Direct LED
Display features	Color gamut (NTSC)	69%
	Operation time	16/7
	Haze (%)	1 %
	Viewing Angle (Right/Left)	178 (89/89) degree
	Viewing Angle (Up/Down)	178 (89/89) degree
MARKET STATE OF THE STATE OF TH	Viewing Angre (Op/Down)	4096 x 2160p (24, 50, 60 Hz
	HDMI Signal	3840 x 2160p (24, 25, 30, 50 60 Hz), 1080p (30, 50, 60 Hz 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
A 45-5	Speaker Position	Down Firing
Audio Specs	Audio Power Output	10W + 10W
	Pro settings	Yes (Simple Pro settings men
Professional	HDMI auto wake-up	Yes
features	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3G8
	Wi-Fi Certified	Yes
Network Specs	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience	On Screen Clock	Yes
features	Sleep Timer	Yes
	On/Off Timer	Yes
	Chromecast built-in	Yes
	Apple AirPlay	Yes
A STATE OF THE PARTY OF THE PAR	IP Control	Yes
Control Specs	RS-232C Control	Yes
Control Specs	HDMI-CEC	Yes
	HDCP	HDCP2.3 (for HDMI1/2/3)

THE RESERVE TO THE RE	HDMI inputs total	3 (3Side)
Inputs and outputs	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)
	Digital Audio Output (s)	1 (Side)
	USB ports	2 (Side)
	Ethernet inputs	1 (Side)
Design features	VESA® Hole Pitch (W x H)	300 x 300 mm
	Rated Power Consumption	226W
Environment Specs	Power Consumption (in Standby)	0.5 W
Livironment specs	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
	Weight of TV without Stand	20.4 kg
Weight	Weight of TV with Stand	21.3 kg
	Weight of Package Carton (Gross)	28 kg